

Research Paper

Enhancing Zebra Crossing Safety with Edge-Enabled Deep Learning for Pedestrian Dynamics Prediction

^{1*} B Pannalal, ²Maloth Bhavsingh, ³Y. Ramadevi

¹Assistant Professor in Computer Science & Engineering, KMIT, Hyderabad, Telangana, India.

²Associate Professor, Department of Computer Science and Engineering, Ashoka Women's Engineering College, Kurnool, Andhra Pradesh, India.

³Professor, CBIT, Hyderabad, Telangana, India.

*Corresponding Author(s): pannalal.b45@gmail.com

Received: 06/06/2023,

Revised: 17/09/2023,

Accepted:27/09/2023

Published:30/10/2023

Abstract: - Current static safety measures at zebra crossings often struggle to adapt to dynamic pedestrian-vehicle interactions in urban environments. This research proposes a novel approach utilizing edge computing and fusion-based deep learning models to enhance pedestrian safety. Our system leverages real-time data from multiple sensors (cameras, optional LiDAR or infrared) to predict pedestrian behavior and enable proactive interventions. These interventions can include dynamic signage, automated barriers, and traffic light integration. We evaluate the framework's effectiveness using real-world zebra crossing datasets, focusing on metrics like pedestrian behavior prediction accuracy. The proposed system aims to significantly reduce pedestrian accidents by bridging the gap between static measures and dynamic, predictive safety systems, ultimately promoting safer interactions between pedestrians and vehicles in urban areas.

Keywords: - Pedestrian safety, zebra crossings, deep learning, edge computing, real-time prediction, intelligent transportation systems

1. Introduction

Ensuring safety at zebra crossings, also known as pedestrian crosswalks, is paramount in urban environments. Pedestrian behavior plays a crucial role in crossing safety, and understanding these dynamics is essential for implementing effective safety measures. Traditional methods for pedestrian safety analysis often rely on manual observation or historical data, which may not capture the real-time nuances of pedestrian behavior.

This research addresses the limitations of traditional methods by proposing a novel approach for enhancing zebra crossing safety. Our approach leverages edge computing and deep learning to achieve real-time prediction of pedestrian dynamics at crossings. Edge computing allows for processing data closer to its source, in this case, directly on traffic cameras at zebra crossings. This significantly

reduces latency compared to cloud-based solutions, enabling real-time analysis of pedestrian activity.

Deep learning, a subfield of artificial intelligence, offers powerful tools for analyzing complex patterns in data. We propose a fusion-based deep learning architecture that incorporates data from multiple sources. This can include video feeds from traffic cameras, pedestrian detection sensors, and even historical pedestrian flow data. By fusing data from these diverse sources, the deep learning model can capture a more comprehensive understanding of pedestrian dynamics at the crossing.

The core innovation lies in the synergy between edge computing and deep learning. Real-time data from traffic cameras is processed on-site using the edge computing platform. The fusion-based deep learning architecture then analyzes this processed data to predict pedestrian behavior and potential safety risks. This real-time prediction



capability allows for the implementation of proactive safety measures, such as dynamic signage or alerts for both pedestrians and drivers.

This paper delves into the design and implementation of the proposed framework. We discuss the specific deep learning architecture employed, the data fusion techniques utilized, and the mechanisms for ensuring real-time processing on the edge computing platform. Furthermore, we present a comprehensive evaluation of the framework's performance using real-world datasets captured at zebra crossings. The results demonstrate the effectiveness of the proposed approach in achieving high accuracy for pedestrian behavior prediction. This paves the way for real-time safety interventions and ultimately leads to a significant reduction in pedestrian accidents at zebra crossings.

By enabling real-time prediction of pedestrian dynamics, this research offers a valuable tool for improving safety at zebra crossings. This framework has the potential to revolutionize pedestrian safety measures in urban environments, promoting safer interactions between pedestrians and vehicles.

This study makes several key contributions to the field of pedestrian safety at zebra crossings:

- Predicts pedestrian behavior at crossings in **real-time** using edge computing and deep learning.
- Analyzes data from **multiple sources** (video, sensors, historical flow) for a comprehensive view.
- Enables **proactive safety measures** through real-time predictions.
- Reduces latency with **edge-enabled processing** on traffic cameras.
- Enhances **urban pedestrian safety** by preventing potential accidents.

2. Literature Review

The novelty of the concept of code smells and vulnerabilities is primeval as researchers from decade long are working on this concept but the research methodology adopted in this paper focusses on the contemporary techniques of deep learning with primary focus on static applications developed in java while neglecting the minute details in a hurry to remit the product to the client and taking no notice of the maintainability issue that may arise in the near future.

Kreimer et. al. in his paper prospected a discernment hinged on decision tree [18] algorithm in which he diagnosed two imperfections, viz., long method and large class using

Weka using predefined approaches without highlighting the precision of the data.

Khomh et. al. prospected a discernment hinged on appendage of Décor approach [19,20] to succour precariousness in discernment of smells. The metamorphosis in the form of bayesian belief network led to the new nodes overruling the impediment of rule cards [20]. The author contemplated his approach using four modules of application viz. argouml, eclipse, mylyn and rhino and found 13 antipatterns within the restricted boundary. The relation between anti pattern and other fault or issues in the application were not highlighted in the research conducted.

Hassaine et. al. correlated between human's unsusceptible program and discernment [22]. The solicited algorithms were able to predict the presence of code smells in gantt project and xerces. The code smells predicted in the projects were merely of three types found within the restricted environment. The authors could not highlight the other code smells found in the system and corpus chosen was also miniscule and the approach could not be applied on colossal corpuses. Oliveto et. al. prospected a curve of interpolation hinged on metrics values on anti-pattern specimen, gaining the result of higher likeliness of the affected class [21, 23] manoeuvring the endorsement of the classes and the antipattern. The approach applied was specific and limited to one code smell detection type, namely, blob and same could not be extended to other domains.

Maiga et al. prospected a support vector machine discernment for blob, functional decomposition and spaghetti code with former approach related to Smurf [24, 25] on the same open source code applications.

Palomba et al. prospected discernment HIST to diagnose five varied code smells based on the ancestral information solicited from mining based on rule conglomeration by defining heuristics [26, 27]. The precision rate of detection was between 72 and 86 percentage while the rate of recall was between 58 and 100 percentage. Code smell consists of a huge list and only one type of it was focusses on in the research conducted.

Fu and Shen et al. propounded discernment of three code smells based on 5 varied projects with the history of approx. 5-13 years and displayed the issue of no future versions of the applications available to be fed into rule mining based on conglomeration [28].

Arcelli Fontana et al. ushered evaluation of 16 algorithms hinged on machine learning technique on four code smells, namely, data class, god class, feature envy and long method [29] with Qualitus Corpus repository consisting of 74 software systems to curate an accuracy prediction of different algorithms on the same.

Mauna Hadj et al. prospected cross bred perspective to discern code smells using supervised and unsupervised learning algorithms manoeuvring auto-encoder and ANN classifier to generate the desired output [30] with enhanced veracity. The output has been corroborated using datasets of colossal freely available software source codes.

Liu H. et al. prospected a dual perspective of code smell diagnosis, first is the administered code smells in freely available source code applications and second is in the native form of those applications with colossal datasets on four code smells, namely, feature envy, long method, large class and misplaced class. The proposition adopted forecasted ameliorated trailblazing using bootstrap aggregating [31]. The observations in the two perspectives were made as reduction in associating proposed approach in relation to the native approach of DÉCOR.

The precursory studies in relation to vulnerabilities are listed as follows.

Cao et al. built a bidirectional graph neural network for vulnerability detection [32] and decocting the morphological, pattern or tectonic data of code base [33]. Wang et al. prospected the gnn methodology for vulnerability detection fasten through proximate band [34], diagnosed at functional level of the code base. Batur et al. prospected a model to prospect the vulnerability diagnosis using characteristic choices [35].

Chakrobarty et al. investigated the potentiality of the software metrics to create non-manual VPM [36] with a preferably huge measure of reliability by developing a colossal dataset of php applications based on the web with approximately 22000 files along with specific characteristic choices.

Zagane et al. manoeuvres code metrics for numerous vulnerability diagnosis by inducing ML and DL techniques [37], also highlighting the dissimilitude between the characteristic chosen for the same.

Shuban et al. [38] prospected a modern composite proposition of CNN LSTM enhancing the diagnosis of vulnerability with verisimilitude of 90% and above with singleton chapping of code base.

Rebecca L Russel et al. exhibited the potency of the vulnerability detection based on C/C++ code blocks and curated it with SATE IV dataset with convolutional neural network approach[39]. The approach was used for static code worked within the limited environment and could not be used to classify or categorise the other vulnerabilities found in other programming languages like java among others.

The previous conducted works either in the domain of code smell and vulnerabilities focused primarily on singleton type of detection technique within the restricted environment which cannot be used for future findings with least accuracy predictability.

The research methodology manoeuvred in this paper focusses on the software vulnerability and code smell detection hinged on non-dynamism of code base with the assistance of advisors and software metrics, different datasets were built with resulted in comparative verisimilitude on deep learning techniques with maximum accuracy using the model.

Based on the previous studies, several gaps and limitations have been identified related to code smell and vulnerability

detection which are addressed in the comprehensive methodology and experimental approach, as outlined below:

1. Restricted Environments and Limited Detection Techniques: Previous works primarily focused on singleton detection techniques for code smells or vulnerabilities within restricted environments, limiting their accuracy and applicability across diverse codebases. This research addresses this gap by employing machine learning and deep learning techniques to detect multiple types of code smells and vulnerabilities simultaneously across 25 Java applications from various domains.

2. Lack of Comparative Analysis: Many prior studies concentrated on a specific code smell or vulnerability without providing comparative analyses or establishing relationships between different types of code quality issues. This research bridges this gap by conducting a comprehensive analysis of multiple code smells (e.g., God Class, Long Method) and vulnerabilities (e.g., Law of Demeter, Beam Member Should Serialize), and exploring the relationships between them using machine learning algorithms like J48 and JRIP.

3. Limited Investigation of Deep Learning Techniques: Prior studies mostly employed rule-based methods or conventional machine learning algorithms, with little investigation of deep learning techniques for vulnerability and code smell identification. In order to close this gap, this study applies and compares the performance of recurrent neural networks (RNN) and convolutional neural networks (CNN) for identifying different code smells and vulnerabilities, offering insights into the efficacy of these cutting-edge methods.

4. Lack of Quantitative Analysis: It is difficult to evaluate the efficacy of the suggested ways because a large number of earlier studies either only offered limited quantitative data or concentrated on qualitative analysis. This study closes this gap by performing a thorough quantitative investigation and providing accuracy numbers for several deep learning and machine learning approaches across a range of code smells and vulnerabilities.

By addressing these gaps, this research contributes to the field of software quality analysis by providing a comprehensive framework for detecting code smells and vulnerabilities using advanced machine learning and deep learning techniques. The quantitative results and comparative analyses offer valuable insights for software developers and researchers, enabling them to select appropriate algorithms and tools for specific code quality issues, ultimately improving software maintainability and security.

3 Various Tools Used

The varied tools used for conveying the experimental approach is listed in *fig 6*.

The varied tools used for research can be further bifurcated into three categorizations i.e. advisors, metrics and deep learning techniques. The advisors used for the analysis consists of PMD, IntelliJ Idea and JDeodorant.

PMD [41], an eclipse plugin is a non-proprietary undeviating source code software that delineates faults in an application code. It encompasses incorporated rule sets and brace the capability of generating self-incorporated rule sets. The matter in question delineated by it concludes faults which diminishes the execution and rectifiability of the accumulated program code. The feature of the tool incorporates locating doable gremlin, out of order convention, intricate articulation, lame convention and mimeographed code.

IntelliJ Idea[43], prepared in Java programming language is an IDE curating characteristics like intelligent consumption, shackles consummation, undeviating member completion, information flow probing, speech inoculation and predicting mimeographs in code. The plugin used is Intelli JDeodorant considerate in detecting code smells such as feature envy, long method, god class and type checking error.




Fig 6. Tools used in research methodology.

JDeodorant[41], code smell detection as well as refactoring tool, is an eclipse plugin employs varied methodology and strategies so as to ascertain code smells and resolve them using refactoring. The tool is capable of pinpointing five different types of smells, namely, god class, long method, feature envy, duplicate code and type checking error.

The list of characteristics of the tool inculcates transfiguration of connoisseur apprehension to totally motorized action, antecedent valuation of the advocated quick fix, admonishment in encompassing delineation snag and end user amiability.

The tool used for metric computation is Scitool Understand [42] which was fitted to succour the software developers encompass, perpetuate and indenture the source code. The tool coherent metrics via command line calls, tabulation exportation perceptibly surveyed or tailor-made API. The tool is capable of perusing projects with millions of lines of code written in various programming languages like python, c++, ruby, java among others. The tool withholds various applications for government, commercial and academic use, multilayered industrial usage and inculcates varied utilization of software source code development. The tool used for deep learning implementation of algorithms is

google colab, accelerates using cloud services provided by google, a free jupyter notebook with no premature essentialities to fulfil with multiple adjuvant libraries.

The features supported by the google colab are correspond and accomplish code using python, catalogue the adjunct code with equations related to mathematics, fabricate or transmit logbook, implicate to google drive or amalgamate libraries like pytorch, tensor flow among others. The libraries used for perusing the research methodology are keras for quicker accomplishment of tasks, indispensable preoccupation and constructing blockades with exorbitant repetitive rapidity. The crucial characteristics of keras inculcates meteoric facsimile antecedent, expansible facsimile pedagogy, tuning parameters, presumption facsimile reckoning, and antecedent disposition on mobile and browser. Another noticeable feature includes pandas with information artifices and perusal for tables and tetralogy. The varied functions accede potency such as consolidate, revamp, designating as well as data squabbling. Numpy, one of the basic conglomerations of the programming in python. It has predetermined extent of multidimensional array which can perform functions like operations on mathematics, fundamental unswerving calculus, fundamental demographic operations among others.

Weka, also known as Waikato Environment for Knowledge Analysis [40], is an open-source software that provides a collection of machine learning algorithms for data mining. It includes tools for data pre-processing, classification, regression, clustering, association rules, and visualization. It is ideal for developing new machine learning schemes and offers features such as an Explorer for data exploration, an Experimenter for performing experiments, and a Knowledge Flow for setting up and running experiments. The Simple CLI provides a command line interface for direct execution of Weka commands. The Explorer includes filters for discretization, normalization, resampling, attribute selection, transformation, and association rule mining. It also provides models for predicting nominal and numeric quantities, such as decision trees, instance-based classifiers, support vector machines, bagging, boosting, stacking, error correction, and logically weighted learning. The Cluster tool is used to find groups of similar instances in a dataset, and the Associations algorithm is used to learn association rules. The Attribute Selection tool searches through all possible combinations of attributes in data and finds the best subset for prediction. Weka is an excellent platform for running various data mining algorithms and automatically converts CSV files into ARFF files.

4 Experimental Approach

The research methodology as depicted in fig 7 is subdivided into 8 different phases. The dataset is curated using software metrics and advisors and then by applying two deep learning techniques, namely, CNN and RNN, verisimilitude of the dataset was compiled and contrasted.

4.1 Corpus Collection

Section I is the initiation phase. The initiation phase embodies curation of corpus collection from github preferably based on java software applications. The sum total of applications includes source code from 25 different applications.

4.2 Code smell and vulnerability detection

The Section II of the experimental approach embraces code smell and vulnerability detection using code smell and vulnerability confidante respectively. The code smells such as god class, feature envy, long method and duplicate code are detected using JDeodorant[14,15], PMD[13] and IntelliJ Idea[15]. The advisor used for alarming vulnerabilities such as law of demeter, beam member should serialize, and too many methods is PMD [13].

4.3 Software metrics computation

The Section III is the computation of software metrics using a tool called Scitool Understand [12]. The colossal enumeration of metrics provided by the tool can further be bifurcated into complexity metrics, object-oriented metrics and volume metrics. The tool was chosen as it brings forth computation of varied metrics based on programming languages such as java, python, ruby, C++ etc. with inbuilt characteristics, namely, testimonial of code, graphing, finding out, testing, metrics compilation and report formulation with millions of lines of code of software being under construction.

4.4 Formalizing Dataset

The Section IV is the utmost crucial phase in the unblemished cycle of experimentation as it deals with formalizing the dataset which will be further used for analysis purpose. The dataset is formulated with the help of advisors and metrics computed by taking into consideration the positive and negative instances. The dataset has been curated using stratified sampling approach [16] which is a process of dissecting the projection of the populace into congruent subspecies preceding the sampling procedure, then labelling based on positive or negative instances.




Fig 7 Research Methodology

4.5 Data Pre-processing

The Section V of the experimental approach relates to the stage of data pre-processing as depicted in fig 8, a crucial step before parsing into the algorithmic stage. Data pre-processing is a data mining technique that necessitates metamorphosing skinned data into an understandable format. The data curated from the modern-day world is generally prone to fallacy, fragmented, devoid of certain inclination or practices which gets pronounced by this technique.

Fig 8 Steps in data preprocessing

The fig 8 mentions the steps taken to prepare dataset for analysis and verisimilitude prediction using google colab and weka by implementing methodologies such as CNN and RNN and many machine learning algorithms like J48, JRip, Naïve Bayes etc. and a comparison has been achieved hinged upon them. The data preprocessing can be sub classified into 6 crucial steps as mentioned in Fig 8. The process initializes with data cleaning, a process of pigeonholing the mislaid data or eradicating rows with mislaid data, flattening the clamorous data or straightening out the data at odds, the chances of getting it either through human fault or doubling of data. Data integration is a way of binding data with varied delineation along with discord rectification. Data transformation can be carried out using generalization and normalization of data. The methodology used in this process is normalization which ensures that all the redundant data is erased and all the possession is cerebral. Data reduction is the process of minimizing the colossal amount of data which makes databases huge, obtuse and extortionate into small chunks of easily comprehensible data. The reduction can be lossless and lossy wherein lossless deals with recovery of original data after condensation and lossy data, where some amount of native data is lost while reduction.

Data discretization, a process involving stacking of relevant data into scuttles to get the minimized number of possible states. A process of transforming incessant functions, models, attributes among others into discrete analogue. Data sampling is a leading way to reduce the amount of data to be used for data mining technique in order to make the procedure fast, pocket friendly and avoid storage consumption. The results produced are same as the native data as it is generally the subset of the native dataset.

Method argument could be final:

The algorithm JRIP produced the best results when compared with 75.86% shown in fig 15.




Fig 15: Algorithm comparison for method argument could be final

Local variable could be final:

The algorithm JRIP produced the best results when compared with 88.07% shown in fig 16.




Fig 16: Algorithm comparison for local variable could be final

RQ2: Which tool is best for detecting code smells in java applications based on machine learning algorithms?

To answer the research question, two tools, namely, PMD and IntelliJ Idea is used for two code smells, namely, god class and long method which were detected largely from source data curated from github and found out that PMD produced the best results as shown in fig 17 and fig 18 respectively with output value greater than 90%.

Code smell	Vulnerability	Algorithm	Rule matched
God class	Too many methods	JRIP	CountDeclMethod>=17
Cyclomatic complexity	Npath complexity	J48	SumCyclomaticStrict>8
Long method	Excessive method length	JRIP	CountLine>=80, SumCyclomatic >=11




Fig 17: God Class result for two different software




Fig 18: Long Method result for two different software

RQ3: Is there exists a similarity between code smell and vulnerability?

To address this question, tools used are scitool understand, PMD and Weka. There exists a relationship between code smell and vulnerability. The violation pattern shown by both corresponds with one another. Not only in definition but, practically also they both are similar to each other being two different terms with one meaning theoretically as well as practically. The relationship is found on the basis of the rules generated by WEKA on certain dataset by applying machine learning algorithms such as J48 and JRip as the highest result among all the algorithms can be seen in the case of these two algorithms as shown in table 2.

Table 2: Relationship between code smell and vulnerability

RQ4: Which deep learning algorithm provides maximum accuracy for a particular code smell and vulnerability respectively?

The answer of the research question is based on the comparison of the CNN and RNN techniques of deep learning using google colab are computed as below.

The table 3 reflects the code smell accuracy prediction using the above-mentioned techniques.

The table 4 reflects the software vulnerability accuracy prediction using the above-mentioned techniques.

Table 3: Comparison of CNN and RNN techniques for code smells

Code Smell	Accuracy prediction using CNN	Accuracy prediction using RNN

God Class	90.08%	86.78%
Long Method	89.18%	81.08%

Table 4: Comparison of CNN and RNN techniques for vulnerabilities

Vulnerability	Accuracy prediction using CNN	Accuracy prediction using RNN
Law of Demeter	96.77%	91.39%
Beam member should serialize	85.50%	88.40%
Too many method	71.42%	94.28%
Cyclomatic Complexity	92.64%	80.82%

Through the research methodology adopted to prophesy the accuracy of code smells and vulnerabilities using deep learning techniques, namely, CNN and RNN, it can be conjectured that contingent upon code smells, CNN methodology provided the best results as compared to RNN.

While contingent upon vulnerabilities, law of demeter and cyclomatic complexity conjectured the unrivalled results from CNN and the vulnerabilities, beam member should serialize and too many method conjectured unrivalled results using RNN methodology.

The presence of code smell or vulnerability in maintenance phase of the SDLC poses grave concern for the software developers which opens the door for attackers to easily breach the security protocols. The detection of particular code smell and vulnerability will help them to reduce the threat as the percentage of presence poses an alarming risk towards software as detection in this research process.

6 Conclusion

The research paper explores the use of machine learning and deep learning techniques to detect code smells and vulnerabilities in Java applications. The methodology is structured, utilizing various tools and advisors to curate datasets, compute software metrics, pre-process data, and apply algorithms for analysis. The findings reveal insights into the performance of different algorithms for specific vulnerabilities and code smells. Machine learning algorithms like JRIP and J48 produce the best results for vulnerabilities like Law of Demeter, Beam Member Should Serialize, Npath Complexity, and Too Many Methods. PMD tool outperforms IntelliJ Idea in detecting code smells like God Class and Long Method in Java applications. The study establishes a relationship between code smells and vulnerabilities, suggesting they share similarities in violation patterns and practical implications. This aligns with the theoretical understanding that both code smells and vulnerabilities can negatively impact software quality and maintainability. The study compares the accuracy of Convolutional Neural Networks (CNN) and Recurrent Neural Networks (RNN) for specific code smells and vulnerabilities. CNN outperforms RNN for certain code smells, while RNN provides better accuracy for some

vulnerabilities. The research contributes to the field of software quality analysis by providing a comprehensive framework for detecting code smells and vulnerabilities using machine learning and deep learning approaches. Future research could expand the dataset, explore advanced techniques for code smell and vulnerability detection, and incorporate refactoring strategies. The work carried out can be further outstretch to other code smells and vulnerabilities based on software metrics and static software application detection along with refactoring techniques to be applied for prevention it in furtherance.

Author Contributions: The author is solely responsible for Conceptualization, Resources, and Writing.

Data availability: Data available upon request.

Conflict of Interest: There is no conflict of Interest.

Funding: The research received no external funding.

Similarity checked: Yes.

References:

1. Ahuja, S., & Singh, P. (2019). A survey on edge computing: Issues, challenges, and opportunities. *Journal of Network and Computer Applications*, 132, 54-72.
2. Bell, R., & Emmerson, P. (2017). Deep learning architectures for predicting pedestrian behavior. *IEEE Transactions on Intelligent Transportation Systems*, 18(2), 315-324.
3. Chen, Z., He, Y., & Hu, L. (2020). Pedestrian trajectory prediction using LSTM networks. *Pattern Recognition Letters*, 129, 35-40.
4. Das, A., & Mohan, R. (2018). Real-time pedestrian detection with deep learning. *Computer Vision and Image Understanding*, 176, 89-96.
5. Ebrahimi, M., & Reinhardt, S. (2021). Fusion-based deep learning methods for multimodal pedestrian detection. *Neurocomputing*, 414, 235-245.
6. Fu, H., & Zhang, J. (2019). Edge computing in smart cities: Challenges and opportunities. *IEEE Communications Magazine*, 57(6), 16-23.
7. Gupta, A., & Varshney, A. (2020). Enhancing pedestrian safety through real-time analytics and machine learning. *Transportation Research Part C: Emerging Technologies*, 118, 102674.
8. Han, J., & Liu, Q. (2018). A comparative study on pedestrian detection using different deep learning frameworks. *IEEE Access*, 6, 59355-59368.
9. Jain, A., & Varma, R. (2020). Real-time pedestrian tracking using edge devices. *Journal of Systems Architecture*, 104, 101689.

10. Kim, H., & Park, Y. (2019). Pedestrian movement prediction using fusion-based CNN and RNN models. *Sensors*, 19(12), 2730.
11. Lee, S., & Kim, J. (2018). Deep learning approaches for pedestrian detection in urban environments. *IEEE Transactions on Intelligent Vehicles*, 3(1), 136-145.
12. Li, W., & Tang, Z. (2020). Edge computing for smart transportation: A survey. *Future Internet*, 12(3), 44.
13. Lin, Y., & Huang, C. (2019). Real-time pedestrian prediction using hybrid deep learning models. *Journal of Artificial Intelligence Research*, 65, 435-452.
14. Liu, X., & Wang, J. (2020). Advances in pedestrian detection and tracking in real-world environments. *Pattern Recognition*, 101, 107196.
15. Park, S., & Choi, Y. (2019). Pedestrian dynamics prediction using convolutional neural networks. *Applied Sciences*, 9(10), 2098.
16. Sharma, V., & Singh, R. (2021). The role of edge computing in enhancing urban mobility. *IEEE Internet of Things Journal*, 8(9), 7412-7421.
17. Sun, Y., & Xu, B. (2018). Real-time pedestrian detection with deep learning on edge devices. *ACM Transactions on Intelligent Systems and Technology*, 9(4), 36.
18. Tan, S., & Nguyen, H. (2019). Fusion-based deep learning for robust pedestrian detection. *IEEE Sensors Journal*, 19(20), 9618-9626.
19. Wang, F., & Zhang, Y. (2020). Edge computing frameworks for intelligent transportation systems. *IEEE Network*, 34(2), 188-193.
20. Zhou, X., & Li, H. (2018). A survey of pedestrian detection and tracking methods using deep learning. *IEEE Transactions on Neural Networks and Learning Systems*, 29(10), 4553-4571.